

Abrasives.....	21	Motor Oil	32
Aerosol Grease.....	31	Multimeters.....	24, 28, 30
Battery Charger.....	13	Nail Puller	19
Brake Oil	34	Nut Drive	20
Buffer Oil	34	Oil Cooler	36
Burnishing Tools	22	Oil Cooler - HydroCool	36
Cable Cutters	19	"Out of Service" Post Its	20
Cement	36	Penetrating Oil.....	31, 34
Chain & Cable Cleaner.....	31	Pit Pads.....	33
Chain Oil.....	33	Pliers	16, 17
Commutator Stones	21	Power Tools.....	13
Commutator Treating Kit.....	21	Punch & Chisel	19
Contact Cleaner	31	Relay Adjustment Tools.....	15
Dash Pot Oil	35	Retrieval Tools	18
Door Closer Oil.....	34	Rope Wear Gauge.....	18
Door Keys	18	Screw Drivers	14, 15
Door Pressure Gauge.....	18	Screws	14
Door Wedge/ Door Stop.....	20	Silicone Spray.....	31
Drill Bits	15	Solvent	36
Fish Tape.....	20	Swaging Tool.....	15
Flexfiles	22	Testers.....	25, 26, 27
Graphite Lubricants	31	Tool Boxes.....	14, 17
Grease & Grease Gun.....	35	Towels	36
Guide Rail Lubricant	31	Wire Puller	15
Hand Tools	14, 16, 17, 18, 19, 20	Wire Rope & Cable Lubricant.....	35
Hydraulic Oil	32	Wire Stripper	17
Inclinometer.....	19	Work Lights	23
IR Thermometers.....	29	Worm Gear Oil.....	33
Level.....	19	Wrenches	16
Liquid Gasket	36		

5383-21

• PISTOL GRIP DESIGN



EXCLUSIVE 5383-21 3/4" ROTARY HAMMER FEATURES:

- 6.0 Amp Motor
- Variable Speed
- Hard Hitting – Hardest Hitting In Its Class 1.7 Ft. Lbs. / Blow
- Fast Drilling – 1,270 RPM And 5,400 BPM
- Cushion Grip – More Comfortable, Secure Gripping
- Lightweight, Compact Size
- Mode Selector Can Be Changed From Hammering With Rotation For Drilling Concrete, To Rotation Only For Use In Steel, Wood, Etc. Using 48-66-1370 Adapter Kit.

SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	BLOW ENERGY (FT.-LBS.)	NO LOAD RPM	NO LOAD BLOWS PER MIN.	SOLID BIT CAPACITY	THIN WALL CORE BIT CAPACITY	LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
5383-21	120	6.0	1.7	0-1270	0-5400	3/4"	1-1/2"	13"	5.7	11.6

NEW

Lok-Tor™ SERIES

0624-24* (KIT)

- T-HANDLE DESIGN DRIVER/DRILL PROVIDES OPTIMUM BALANCE AND COMFORT
- 1/2" ALL METAL RATCHETING KEYLESS CHUCK



495 IN.-LBS. TORQUE!

- **Powerful 18 Volt Motor**
Develops 495 in.-lbs. maximum torque.
- **1/2" All Metal Single Sleeve Grip-Lok™ Ratcheting Chuck With Carbide Jaws For 25% More Grip-Strength**
- **18 Volt, 2.4 Amp-Hr Battery**
Delivers more run time and is compatible with all other MILWAUKEE 18 volt products.
- **Reversible Battery Pack***
Fits into tight work spaces and adjusts balance.
- **One-Hour Universal Charger**
- **Two Speed Ranges: 0-500 And 0-1700 RPM**
- **World's First Dampened Spindle-Lock**
No "clunk" when the trigger is released.
- **Side Handle Rotates 360° And Provides Ultimate User Control During High Torque Applications**
- **Ergonomic Soft Finger Grip For Enhanced Comfort**
- **20-Position Torque Adjustment**



SPECIFICATIONS

CATALOG NUMBER	VOLTS DC	DRILL SPEED RPM HIGH LOW	NO LOAD BPM	DRILL MAX. TQ. IN.-LBS.	BATTERY AMP-HRS	LENGTH (INCHES)	NET WGT. LBS.	SHIP. WGT. LBS.
0624-24 KIT	18	0-1700 0-500	—	495	2.4	10-1/2	4.0	15.1

SPECIFICATIONS

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT.* LBS.	SHIP. WGT. LBS.
0300-20	1/2"	120	8.0	0-850	DOUBLE	1/2-20	48-66-1355	48-66-3280	12-13/64	5.4	5.9



0300-20

• WITH KEYED CHUCK



ERGONOMIC TACTILE GRIP ON HANDLE AND MOTOR HOUSING



6514-21*



- **6-Position Rotatable Handle*** Allows User To Get Between Joists, Studs And Other Confined Spaces
- **Orbital Action Selector*** For Aggressive Wood Cutting
- 0-2,700 SPM
- 3/4" Blade Stroke
- **18 Volt, 2.4 Amp-Hr Battery**
Delivers the most run time and is compatible with all other MILWAUKEE 18 volt products.
- **One-Hour Universal Battery Charger**
- **Reversible Battery***
Allows easier plunge cutting.
- **Counter Balanced Mechanism** Ⓢ
Reduces vibration.
- **Durable Slider-Crank Reciprocating Mechanism** Ⓢ
Withstands abrupt stalls and abusive job-site applications. Designed for compact size and efficiency for cordless applications to maximize run-time. ■ **Heavy-Duty Milwaukee Built Motor** Ⓢ
- **Double-Walled Rotating-Handle Detents** Ⓢ
Provide extremely strong pivoting mechanism.
- **Metal Cam Lock** Ⓢ
Provides a firm hold in each pivoting position, particularly in high vibration.
- **25 Amp Marquardt Variable Speed Switch** Ⓢ
- For greater user control and long life.
- **Heavy-Duty, Steel, Keyless Quik-Lok Blade Clamp™**** Ⓢ
For fast easy blade changes. No hex key to lose or screws to strip. Accepts standard 1/2" shank Sawzall blades.
- **Soft-Grip Handle Pad For Comfort And Secure Gripping** Ⓢ
- **All Metal Gearcase** Ⓢ
- **Rugged, Tool-Free Adjustable Shoe**** Ⓢ
- **Orbit Adjustment Lever** Ⓢ
- **Replaceable Brushes** Ⓢ

*Patent Pending
**Patented

6537-22



10 AMP MOTOR 0-3200 SPM QUIK-LOK BLADE CLAMP™



SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	STROKES PER MINUTE	STEEL QUIK-LOCK BLADE CLAMP	IMPACT PROTECTION	LENGTH OF STROKE	OVERALL LENGTH	NET WGT. LBS.	SHIP. WGT. LBS.
6537-22	120	10	0-3200	YES	YES	1-1/4"	17-7/8"	8.8	15.3

STANDARD EQUIPMENT: FOR 6537-22 – Includes Super Sawzall with Steel Quik-Lok Blade Clamp, Impact Resistant Carrying Case, 8' 3-Wire Quik-Lok Cord and Super Sawzall Assortment Two Blade Pack 48-02-5055.

SPECIFICATIONS

0375-6
• 3/8" CLOSE QUARTER DRILL

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP WGT. LBS.
0375-6	3/8"	120	3.5	0-1300	DOUBLE	1/2" - 20	48-66-2115	48-66-3240	6-1/2	3.0	3.5



NEW

Lok-Tor™ SERIES

0616-24* (KIT)

- T-HANDLE DESIGN PROVIDES OPTIMUM BALANCE AND COMFORT
- 1/2" ALL METAL RATCHETING KEYLESS CHUCK



* TOOL AVAILABLE WITHOUT BATTERY CHARGER OR CASE. SEE "O" MODELS IN SPECS CHART BELOW



460 IN.-LBS. TORQUE!

NEW! ALL-METAL RATCHETING CHUCK WITH CARBIDE JAWS



SPECIFICATIONS

CATALOG NUMBER	VOLTS DC	SPEED RPM HIGH	SPEED RPM LOW	DRILL MAX. TO. IN.-LBS.	BATTERY CAPACITY A-HRS.	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
• 0616-24	14.4	0-1700	0-500	460	2.4	10-1/2	3.7	13.5

SPECIFICATIONS



0200-20
• WITH 3/8" KEYED CHUCK



CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP WGT. LBS.
0200-20	3/8"	120	7.0	0-1200	DOUBLE	1/2"-20	48-66-0806	48-66-3080	12	4.2	4.7

SPECIFICATIONS

CATALOG NUMBER	SPEED RPM	DISC DIA.	VOLTS AC-DC	OUTPUT (WATTS/MAX HP)	AMPS	THREAD SIZE*	LENGTH (IN.)	WIDTH (IN.)	WGT. LBS.	WGT. LBS.
6148-6	10,000	4-1/2"	120	1200/1-2/3	8.5	5/8"-11	14	5	4.9	6.1

6148-6
• 4- 1/2" SANDER/GRINDER WITH LOCK-ON



NEW

48-59-0260

• MULTI-BAY CHARGER



JOB SITE TOUGH!

MULTI-BAY CHARGER 48-59-0260

- Charge Up To Three Battery Packs Of The Same Or Other Voltage Simultaneously
- Fast Charging In 45 Minutes For Minimal Down Time
- Micro-Controlled Conditioning Mode Maximizes Run Time Automatically During Each Charge Cycle
- Generator, Inverter And Long Extension Cord Ready - Due To Wide Input Voltage Range Of AC Charger
- Durable Construction Protects The Charger In Harsh Job Site Environment
- For Use With All Milwaukee Slide-On Style Battery Packs
- ② Dust Cover Protects Charger Terminals From Job Site Contamination and Debris
- ③ Automatically Retracts When A Battery Is Inserted
- ④ 9" Cord With Pass Through Plug
- ⑤ High Visibility LED Indicators Let You Know What Charging Stage The Battery Pack Is In
- Convenient Cord Wrap Also Acts As A Shock Absorber If The Unit Is Tipped Or Dropped
- Impact Resistant Base Provides Ultimate Protection In Job Site Conditions
- Withstands 8" Drop To Concrete (With Battery Packs Attached)

5359-21

- 1-1/8" CAPACITY
- 0-980 RPM
- CHIPPING MODE



- **D-Style Handle**
Offers a secure grip that maximizes drilling pressure while minimizing operator fatigue.
- **Electronic Variable Speed Control Trigger**
For smooth, controlled starts and hammering with rotation in concrete and masonry or drilling without hammering in wood or metal.
- **Slip Clutch**
When bit jams, the clutch slips - rotary action stops.

EXCLUSIVE 5362-6 FEATURE:

- **Reversing Switch**

SPECIFICATIONS

CATALOG NUMBER	VOLTS AC ONLY	AMPS	RPM	REMOVEABLE SDS BIT HOLDER	BLOW ENERGY (FT.-LBS.)	BLOWS PER MIN.	SOLID BIT CAPACITY	WOOD FLAT BORING BIT	STEEL TWIST DRILL	CORE BIT CAPACITY	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
5359-21	120	7.4	0-980	NO	2.5	0-4200	1-1/8"	1-1/2"	1/2"	4"	13"	8.3	14.5



TOOL BOXES

Classic-styled tool boxes for protecting and toting your special gear. Made from durable black fiber material with metal-reinforced corners, double latches, top handle, and one or two concealed side drawers.

A700. Tool Box, 12½"W x 6½"H x 5½" deep; one drawer.

A701. Tool Box, 14½"W x 8½"H x 7½" deep; two drawers.

A702. Shoulder Strap, fits either tool box.

MULTI-BIT 16-IN-1 SCREWDRIVER

Ratcheting and pivoting screwdriver stores 8 double-ended bits in handle, for total of 16...PLUS 6 assorted sockets.

Slot, Philips, hex, hex security, and spanner bits handle nearly every worksite driver requirement. Bits can be used in power and other manual screwdrivers.

Handle pivots 90° in 2 directions.

ATL101. Screwdriver with 8 bits, 6 sockets, pivot, ratchet.

A590A. Screwdriver with 8 bits only. *Add your co. name!*

ECONOMICAL 4-BIT SCREWDRIVER

A571A1 Spanner/Phillips/Slotted All-in-One Screwdriver.

Four drivers in one. Two double-sided driver bits (one stores in handle): #8/#10 spanner, #2 Phillips, & slotted. Bits are held securely by double-ended shaft.

Replacement heads available. Order **A571A3** for Phillips/slotted bit; **A571A2** for spanner.

Impact Driver

This is THE tough, gutsy tool for loosening and removing seized screws and bolts. Heavy-duty handle accepts six work bits (3 blade, 3 Phillips, included).

A719. Impact Driver with 6 bits.

Also Available
A719A 4 Bit Set
A719B 6 Bit Set



EXTRA LONG (3") DOUBLE-ENDED BITS*

Adams part no.	Description
ATL115	Hex Security 1/8" - 5/32"
ATL116	Spanner 4 - 6
ATL117	Spanner 8 - 6
Standard Bits:	
ATL110	Slot 5/32" - 7/32" a
ATL111	Slot 3/16" - 1/4"
ATL112	Phillips #0 - #1
ATL113	Hex 3/32" 1/8"

*Hardened S2 Steel, universally-sized for use in power tools

SPANNER DRIVE, OVAL HEAD (50/PK)

Adams part no.	Description
A573A	8-32 x 1/2", nickel plated
A573B	8-32 x 1", nickel plated
A573C	10-32 x 1/2", nickel plated
A573D	10-32 x 1", nickel plated
A573F	8-32 x 1/2", brass
A573G	8-32 x 1", brass
A573P2	8-32 x 2 1/2", brass
A573H	10-32 x 1/2", brass
A573J	10-32 x 1", brass
A573P6	10-32 x 2 1/2", brass
A573P4	8-32 x 2 1/2", nickel plated
A573P8	10-32 x 2 1/2", nickel plated

VANDAL-RESISTANT SCREWS

Available in stainless or brass. Choose 8-32 and 10-32 thread sizes. Use with one of our spanner head screwdrivers; 50 screws/pkg.

TINNERMAN CLIPS (10/PK)

Adams part no.	Description
A573M	#8-32 Tinnerman clips
A573Q	#10-32 Tinnerman clips

PHILLIPS DRIVE, OVAL HEAD (50/PK)

Adams part no.	Description
A573K	#8-32 x 3/4" brass screws
A573L	#8-32 x 3/4" nickel-plated screws
A573N1	#10-32 x 3/4" brass screws
A573N2	#10-32 x 3/4" nickel-plated screws
A573N3	#10-32 x 1" brass screws
A573N4	#10-32 x 1" stain. steel screws
A573P1	#8-32 x 2 1/2" brass screws
A573P3	#8-32 x 2 1/2" nickel-plated screws
A573P5	#10-32 x 2 1/2" brass screws
A573P7	#10-32 x 2 1/2" nickel plated

SWAGING TOOL AND BUTTON GUIDE

Here's an indispensable tool combo for installing O450-, O451-, and O467-series replacement Otis pushbutton guides.

For studless buttons, just slip the guide onto the threaded bolt...slide assembly through button cutout in panel...and tighten down with 3/4" wrench. Remove swaging tool, and button guide stays locked firmly in place for no-miss button installation. Saves mechanics' hands and time.

O457 Swaging tool and button guide.

P.I. LENS EXTRACTOR

Change Westinghouse "Time Saver" P.I. bulbs quickly and easily from the front with this specially-designed lens removal tool.


Suction-cup gripper with convenient screw-on handle (2"L) makes bulb replacement fast and simple.

W459T P.I. lens extractor.

RELAY ADJUSTMENT TOOLS

Put these time-saving tools in every mechanic's tool box and watch productivity soar. All models feature insulated handles.

A560-series Relay adjustment tools.



ESCALATOR STEP REMOVING TOOL

Use 2 of our step removal tools (replaces Otis' tool No. 9) for the leverage you need to work on worn escalator step treads.

OE930T9 Escalator step removing tool.

CONTACT BURNISHERS

Non-residual tools burnish away oxidation on silver contact surfaces.

A561B1 Contact burnishers. 4"L x 3/16"W x 0.007" thick; 10 per pkg.

A561B2 Contact burnishers. 3 5/8"L x 1/4"W x 0.010" thick; 10 per pkg.

O-RING REMOVING TOOLS

Two special double-ended brass tools simplify removal and replacement of O-rings. Pry, pull, push, and stretch O-rings easily. Brass material prevents damage to surfaces.

DV55GT1 O-ring removing tools.

A560-SERIES RELAY ADJUST. TOOLS

Adams part no.	Description
A560W1	Wrench, 6 3/8" long; offset 0.018"
A560W2	Wrench, 6 3/8" long; offset 0.020"
A560W3*	Wrench, 6 3/8" long; offset 0.032"
A560W4	Spring adjustor, 5" long; 0.031"

*Not shown

WIRE PULLER

Takes much of the hard work out of tedious wiring jobs; reaches where fingers can't to pull wire through narrow openings. Insulated handle. Slot width is 0.050".

A563 Wire puller.

RETAINING RING PLIERS

Dual-purpose model services internal and external retaining rings. Comes with 4 interchangeable tips, Allen wrench, and insulated handles. Master-mechanic quality for long service.


A570D Retaining ring pliers.

A570D1 Replacement tip kit for A570D pliers.

OFFSET SCREWDRIVERS

Forged steel tools for heavy-duty performance; slotted and Phillips heads, round shafts.

A571-series Offset screwdrivers.



HEAVY-DUTY DRILL BITS

The 4 cutting edges on our M-7 steel drill bits retain their cutting edges under near-red-hot operating conditions. Modified split points for accurate centering. These bits hold a sharp edge up to twice as long as regular drill bits.

Choose convenient 9-piece assortment (A574S, 1 ea. of the sizes shown in the table), or multi-packs of single sizes; same-size shanks (see photo, above).

A574-series Heavy-duty drill bits.

Adams part no.	Description
A571B	2 slotted blades, 90° to handle
A571C	1 slotted, 1 No. 2 Phillips blade; 90°
A571P	No. 1 Phillips/No. 2 Phillips; 90°

Adams part no.	Drill bit diameter	# bits per set	Adams part no.	Drill bit diameter	# bits per set
A574S	1/16" thru 1/2"	9	A574F	1/4"	6
A574A	1/16"	6	A574G	5/16"	4
A574B	3/32"	6	A574H	3/8"	4
A574C	1/8"	6	A574J	7/16"	4
A574D	3/16"	6	A574K	1/2"	4



ATL320 Multi-plier puts three popular tools at your fingertips

ATL324 Long-nose plier strips 0.3" wire

ATL325 Diagonal-cutting plier strips 0.03" and 0.05" wire

3-IN-1 MULTI-PLIER

Our redesigned multi-plier replaces three of the most commonly-used pliers with one double-hinged mechanism. The double hinge multiplies the cutting leverage at the jaw.

You get three interchangeable carbon steel plier heads, induction-hardened for exceptional strength: long nose, diagonal cutting, and combination. Heads change easily with-out tools: unlock handles ...open fully...pull out head...insert new head...close handles.

Other features include precision-engineered cutting edges, spring-loaded PVC handles, rugged holster,

lifetime warranty on the mechanism, 3-year warranty on the heads.

ATL320 3-In-1 Multi-Plier with holster and three interchangeable heads.

LONG-NOSE PLIER

Our chrome-vanadium alloy long-nose plier comes with all the features of our diagonal-cutting plier, in a long-nose model.

Use anywhere a long-nose plier is needed, with the confidence of knowing that you can't work with a better-made tool.

ATL324 Long-Nose Plier with holster.

DIAGONAL-CUTTING PLIER

Our professional-quality diagonal-cutting plier boasts a precisely-honed cutting edge and a skinning slot for stripping wire. Includes a rugged holster.

Made from drop-forged chrome-vanadium alloy, this fine tool includes a crimper feature between the handles...an induction-hardened cutting edge...and a hot-riveted joint.

ATL325 Diagonal-Cutting Plier with holster.

All three specialty pliers come with a rugged, convenient holster that attaches to clothing or tool belt



ADJUSTABLE WRENCHES

With spans 18% wider than normal, the jaws of our adjustable wrenches feature a ridge design that catches different-size fasteners without stripping.

Precision joint mechanism has been engineered for smooth, no-wobble operation, and laser-etched gauges (inches on one side and millimeters on the other) give uncommon convenience and accuracy.

Industry-quality chrome-vanadium steel lends superior strength; streamlined handle with oversize grip improves tool balance and reduces hand fatigue.

ATL304 Adjustable 6" Wrench.

ATL305 Adjustable 8" Wrench.

ATL306 Adjustable 10" Wrench.

ATL307 Adjustable 12" Wrench.

8-IN-1 MULTI-WRENCH

8-in-1 Multi Wrench gives you four different SAE wrench sizes at each end. Pack one of these instead of eight separate wrenches: $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{7}{16}$ ", $\frac{1}{2}$ ", $\frac{9}{16}$ ", $\frac{5}{8}$ ", $\frac{11}{16}$ ", and $\frac{3}{4}$ ". Chrome vanadium hardened steel shank. Soft comfort grip is 5" long. Overall length: $8\frac{3}{8}$ ".

ATL301 8-in-1 Multi-Wrench.

Heavy-Duty Slip-Joint Pliers

These big-muscled pliers feature a solid shaft that holds true under the tightest grip. Replaces the classic bolt-and-groove plier with a double-sided steel shank. This bolt-less, rivetless jaw mechanism can't slip or torque out.

The soft, non-slip grip provides extra space between the handles to protect fingers...even at full jaw extension.

Forged from industrial-strength chrome-vanadium steel for greatest possible strength; warranted for life.

ATL321 10" Slip-Joint Pliers.

ATL322 12" Slip-Joint Pliers.

ATL323 16" Slip-Joint Pliers.

10" & 14" Self-Adjusting Pipe Wrenches

Our tough Self-Adjusting Pipe Wrenches combine the convenience of a pivoting head and ratcheting tension adjustment. Grab the workpiece from almost any angle and tighten with one-hand ratcheting motion. 360° swivel head lets you apply leverage in tight spots.

ATL302 10" Ratcheting Pipe Wrench.

ATL303 14" Ratcheting Pipe Wrench.

**ATL336****ATL337****ATL373****ATL374****ATL376****ATL378****APL109T****ATL381****WIRE STRIPPER**

Automatic action top loading stripper grips and cuts cleanly with one squeeze. Self adjusting, designed for 10 -26 AWG wire, solid or stranded.

AT336 Wire Stripper.

10" CUTTER STRIPPER

Cuts soft copper wire with one end, grabs and strips with the other. Stripper self-adjusts to wire size - no stripping holes to locate. Use on soft copper (electronic) wire sizes 26 to 14 AWG. Cutting head is full-flush cutting and low-profile with stainless steel, induction-hardened jaws.

ATL337 2 in 1 Cutter/Stripper.

10" HEAVY-DUTY CRIMPING PLIERS

Oversized cross section for super heavy-duty jaws. Induction-hardened cutting edges and hot-riveted joints. Industrial quality chrome vanadium.

ATL373 Heavy Duty Crimping

HEAVY-DUTY LINESMAN PLIERS

Oversized cross section for super heavy-duty jaws. Induction-hardened cutting edges and hot-riveted joints. Industrial quality chrome vanadium.

ATL374 9.5" Heavy Duty Linesman Pliers

ATL375 8.5" Heavy Duty Linesman Pliers

HEAVY-DUTY DIAGONAL-CUTTING PLIERS

Oversized cross section for super heavy-duty jaws. Induction-hardened cutting edges and hot-riveted joints. Industrial quality chrome vanadium.

ATL376 7" Heavy Duty Diagonal Cutting Pliers

ATL377 8" Heavy Duty Diagonal Cutting Pliers

8 " HEAVY-DUTY LONG-NOSE PLIERS

Oversized cross section for super heavy-duty jaws. Induction-hardened cutting edges and hot-riveted joints. Industrial quality chrome vanadium.

ATL378 9.5" Heavy Duty Long-Nose Pliers

ELECTRONIC DIGITAL CALIPER 6"/150MM

6" Caliper features zero setting at any position. Conversion switch provides instant conversion between millimeters and inches Stainless steel shaft. Display has automatic shut off . Uses one battery, type SR44 (included). Shaft displays measurements in inches and millimeters.

ATL381 Electronic Digital Caliper

TOOL BOX

Heavy-duty, molded plastic (without tray). 19.6" x 10.4" x 9.8"

APL109T Tool Box



DOOR KEY VALUE PAK

Put every door key you'll ever need into your toolbox...and save significantly compared to the cost of buying them individually.

This seven-piece Value Pak includes keys for Dover, GAL, Otis, and Westinghouse. Helps you streamline every service route by equipping each mechanic for the unexpected.

KVP840 Key Value Pak opens doors to increased productivity.

INSPECTION MIRROR

Magnifying inspection mirror lets installers check hard-to-see connections, contacts, and other obstructed-view components. 1 1/8"-dia. mirror is mounted at 45° angle to see around corners. Insulated handle; overall length = 6 3/8".

A565. Inspection Mirror.

TELE-MIRROR LOCATOR TOOL

Telescoping mirror extends to 27 1/2" for locating items dropped behind or under obstacles...especially helpful when working on escalators.

Mirror surface is 2 1/2" x 1 3/4". Non-slip black handle makes this tool easy to use.


A722. Tele-Mirror locator tool.

TELE-MAG RETRIEVAL TOOL

Telescoping magnetic retrieval tool extends to 29" to help you retrieve small metal objects that have been dropped or rolled out of reach.

Holds up to 6 lbs.

A723. Tele-Mag retrieval tool with protective cap.



GAL JUMPERS

Here are the tools mechanics need for jumping GAL doors during servicing.

G30L3 "Tomahawk" with MO jumper head and 10 1/2"L looped handle. Replaces GAL part no. INT-2-24 & INT-1-19.

G30L2 Double-barrel contact head.

G30L1 Combination MO jumper head does the job of both jumpers above; no handle.

DOOR PRESSURE GAUGE

Measures closing pressure of elevator doors to help mechanics make adjustments without guesswork.

TO USE: Let door close about half way, and stall it with your foot. Hold gauge firmly against door...release foot...keep door from moving for 5-10 secs. Read closing pressure at location of O-ring. (Range: 0-35 lbs.)

A568 Door Pressure Gauge helps keep closing pressure within code.

TELESCOPING LIGHTED PICKUP AND MIRROR KIT

Pickup features bright white LED light at the tip on a chrome-plated shaft that telescopes to 24". Super strong 5 lb. magnet is encased in a brass shield that directs the magnetic force to the tip - won't attract peripheral objects. Light turns off when not in use. Uses 3 type 357 button cell batteries (included). Mirror has a universal joint that adjusts to any angle, and a chrome-plated shaft that telescopes to 36", collapses to 8"; in fitted case.

ATL369 Telescoping Lighted Pickup and Mirror Kit

ATL369T Telescoping Lighted Pickup



ROPE WEAR GAUGE

Pocket sized aluminum tools helps mechanics and inspectors with initial field determination of a wire rope's diameter and whether or not the diameter may be worn beyond allowable specifications. Precision CNC machined from T6061billet aluminum, color anodized and laser etched for easy use and recognition.

If gauge fits over rope, rope is worn beyond allowable specification and should be inspected further. To meet the industry needs and accommodate current and ongoing code revisions and proposals, four (4) models of wire gauge are now available to meet your needs. Our A17.1 code compliant gauge, is complimented by several additional gauges designed to conform to the proposed A17.6 code revisions, including allowances for measuring for both wear and rouge.



ATLOOM



ATL001

Adams part no.	Description
ATL096	(A17.1 code compliant) – Imperial wire rope wear gauge (7 slot) – Black color. For the following rope diameters: 3/4", 11/16", 5/8", 9/16", 1/2", 7/16", 3/8".
ATL001	(A17.6 proposed code revision) – Imperial wire rope gauge – with ROUGE (7 slot) – Red color. For the following rope diameters: 3/4", 11/16", 5/8", 9/16", 1/2", 7/16", 3/8".
ATLOOM	(A17.6 proposed code revision) – Metric wire rope gauge – with ROUGE (7 slot) – Blue color. For the following rope diameters: 22, 19, 16, 13, 11, 10, 8 mm.
ATLOOKM	(A17.6 proposed code revision) – Metric wire rope gauge – with ROUGE (8 slot) – Blue color. For the following rope diameters: 19, 16, 13, 11, 10, 9-1/2, 8, 6 mm.



ATL096



ATLOOKM



NAIL PULLER/PRY BAR

This tougher-'n-nails wrecking tool pulls nails at one end, and gives you superior leverage from the other end for opening crates and lifting heavy objects.

Hexagonal bar stock of tempered steel. 18" long. Use anywhere the job calls for an unyielding tool.

ATL404 Nail Puller/Pry Bar.

PUNCH & CHISEL SET

Our 9-piece set gives you a variety of commonly-needed punches and cold chisels. Chisels feature Targethead® design to reduce spalling and mushrooming.

Contents: Two cold chisels (1/2" and 3/4" points); one 5"L prick punch, 3/8"; one 4 1/2"L center punch, 5/16"; three pin punches, 1/16", 3/32", and 1/8"; and two drift punches, 1/8" and 3/16".

ATL402 9-Piece Punch & Chisel Set.


CABLE CUTTERS

Cuts stranded cable cleanly with no frayed edges. High-quality tool manufactured of aircraft quality alloy steel with heat treated cutting edges. Powder-coated handle for longest life.

ATL365 18" Cable Cutters.

ATL368 42" Cable Cutters.

ATL368



NAIL SETS

Our 4-piece set gives you commonly-needed sizes in hardened steel with knurled, slip-resistant shafts: 1/32", 1/16", 3/32", and 1/8".

ATL403 4-Piece Nail Set Kit.

Constructed of durable aluminum alloy, our inclinometer is designed for rugged use under all working conditions.

ATL500 Industrial Inclinometer.

INDUSTRIAL INCLINOMETER

This fully-professional tool reads angles instantly and accurately to a tolerance of 0.5°.

Angle and grade chart shows angles in degrees and converts them to pitch per inch and pitch per foot.




ATL331

9" TORPEDO LEVEL

Features magnetic strip, top-read window. 3 vials: one plumb, one level, one 45 deg. Tinted 360 deg. vials for easy reading.

ATL331 9" Torpedo Level.



DIAMETER TAPE MEASURE

Measures diameter in centimeters and inches. Perfect for accurate measurement of hydro piston diameter. A "must have" for every toolbox.

A560D Diameter Tape Measure.

"Out of Service" Post-It™ Signs

Easy-to-use caution signs feature 3M™ "Post-It Note" removable adhesive. Simple, economical way to inform riders when an elevator has been taken out of service.

Press on, peel off; will not harm sensitive finishes or materials. Red ink on white paper. Fifty self-adhesive 4" x 6" signs per pad, 20 pads per package.

A559 "Out of Service" Post-It™ Signs, 20 pads of 50 signs each.

NUT SLEEVE INSTALLATION TOOL

Reduces sheet metal mounting jobs to three quick & easy steps: 1) Drill a hole. 2) Install a nut sleeve. 3) Drive a screw.

Set up every mechanic with a nut sleeve tool, and watch mounting problems go away. Features insulated comfort-grip handle; accepts all mandrells and sleeves listed below (mandrell bushing set and nut sleeves sold separately).

A550T1 Nut sleeve installation tool.

Size	Mandrell bushing set	Nut sleeves (50/pkg)
#6-32	A550M1	A550NS1
#8-32	A550M2	A550NS2
#10-24	A550M3	A550NS3
#10-32	A550M4	A550NS4
1/4"-20	A550M5	A550NS5
1/4"-28	A550M6	A550NS6
5/16"-18	A550M7	A550NS7
5/16"-24	A550M8	A550NS8

HOLLOW SHAFT NUT DRIVER SET -

7 PC. SAE

Includes 7 SAE sizes: 3/16", 1/4", 5/16", 11/32", 3/8", 7/16", 1/2". Color coded hollow shafts accommodate longer fasteners. Extra-deep sockets securely grip nuts and bolts.

ATL371 Hollow Shaft Nut Driver Set - 7 Pc. SAE.

ATL371



ALSO AVAILABLE....

Adams part no.	Description
A550NS9	ADAMS, THD INSERT, M4X0.7 AK (25 PCS)
A550NS10	ADAMS, THD INSERT, M5X0.8 AK (25 PCS)
A550NS11	ADAMS, THD INSERT, M6X1 AK (25 PCS)
A550NS12	ADAMS, THD INSERT, M8X1.25 AK (25 PCS)
A550NS13	ADAMS, THD INSERT, M10X1.5 AK (25 PCS)
A550CK14	CONV KIT METRIC TSN TYPE M4X0.7
A550CK15	CONV KIT METRIC TSN TYPE M5X0.8
A550CK16	CONV KIT METRIC TSN TYPE M6X1.0
A550CK17	CONV KIT METRIC TSN TYPE M8X1.25
A550CK18	CONV KIT METRIC TSN TYPE M10X1.5



ATL326

ELECTRICIAN'S FISH TAPE

ATL326 50-ft. Electrician's Fish Tape.

ATL327 100-ft. Electrician's Fish Tape.

SAF164



SAF165

DOOR WEDGE

SAF164 Door Wedge - Standard.

SAF165 Door Wedge - Deep Sill.



ATL363

BALL AND HEX KEY SET - 7 PC. SAE

Includes 7 SAE sizes: 1/16", 5/64", 3/32", 7/64", 1/8", 9/64", 7/32". High impact plastic handle. Hardened chrome vanadium steel is finished to resist rust.

ATL363 Ball and Hex Key Set - 7 Pc. SAE.



LATHE-TYPE COMMUTATOR STONES					
Adams part no.	Grit/Grade	Dimensions			Wood block
		L	W	H	
A5610A1 A5610A2 A5610A3 A5610A4	90/M 120/F 220/P 320/E	5"	1 1/2"	1"	1 1/2"W
A5610B1 A5610B2 A5610B3 A5610B4	90/M 120/F 220/P 320/E	5"	2"	1"	3"W
A5610C1 A5610C2 A5610C3 A5610C4	90/M 120/F 220/P 320/E	8"	1 1/2"	1"	1 1/2"W
A5610D1 A5610D2 A5610D3 A5610D4	90/M 120/F 220/P 320/E	8"	2 1/2"	1 1/2"	3"W

Use our line of commutator stones to dress and finish worn commutators. Clean up the resulting burr with a "Rubrite" flexible abrasive brick. And finish the job by shaping carbon brushes to conform to commutator surfaces with a brush seating stone.

Everything you need for commutator maintenance is included in our exclusive 13-piece Commutator Treating Kit (part no. A5613A1, pictured below).

TECH NOTE:

As a general rule, large and badly worn commutators require initial dressing with a coarse stone; smaller commutators often can be treated with medium- and fine-grade stones.

The smaller the contact, the finer the grit of burnishing tool you can start with.

Different styles and grades of stones and burnishers might need to be tested to find the combination and sequence of grits that works best.

PENCIL-TYPE COMMUTATOR STONES				
Adams part no.	Grit/grade	Dimensions		
		L	W	H
A5610E1 A5610E2 A5610E3 A5610E4	90/M 120/F 220/P 320/E	6"	3/8"	1/4"
A5610F1 A5610F2 A5610F3 A5610F4	90/M 120/F 220/P 320/E	6"	1/2"	1/4"
A5610G1 A5610G2 A5610G3 A5610G4	90/M 120/F 220/P 320/E	6"	3/8"	3/8"
A5610H1 A5610H2 A5610H3 A5610H4	90/M 120/F 220/P 320/E	6"	1/2"	3/8"
A5610J1 A5610J2 A5610J3 A5610J4	90/M 120/F 220/P 320/E	6"	5/8"	1/2"
A5610K1 A5610K2 A5610K3 A5610K4	90/M 120/F 220/P 320/E	6"	3/4"	3/4"

"RUBRITE" FLEXIBLE ABRASIVES			
Adams part no.	Dimensions		
	L	W	H
A5611A1 A5611A2 A5611A3 A5611A4	5"	3/8"	3/8"
A5611A5 A5611A6 A5611A7 A5611A8	5"	3/4"	3/4"

BRUSH SEATING, CLEANING STONES					
Adams part no.	Dimensions			Grade	Qty./box
	L	W	H		
A5612A1 A5612A2 A5612A3	4 3/4"	2"	1 1/4"	Med. soft	1
A5612A4 A5612A5 A5612A6	4 3/4"	1 1/2"	1/2"		
		3/4"	1/2"		

COMBINATION COMMUTATOR STONE				
Adams part no.	Grits (grades)	Dimensions		
		L	W	H
A5610L1	90/220 (M/P)	8"	2"	1"

Adams' exclusive Commutator Treating Kit (part no. A5613A1) packs into a convenient storage box everything you need for thorough commutator maintenance:

- 2 ea. Coarse, Med., Finish, and X-Finish
- 4 Firm/Hard seating stones;
- 1 stone holder;
- 1 storage case


COMMUTATOR TREATING KIT

A5614A3

A5614A2

Replacement stones available (6/pkg.):

- A5614A1** Coarse
- A5614A2** Medium
- A5614A3** Finish
- A5614A4** X-Finish
- A5614A5** Firm/Hard Seating



Clean contacts the easy way with our "Plastone" flexible files to remove damaged contact material.

Files can leave a non-conductive residue on the face of a contact. This residue must be removed for safe and reliable operation. For fine contacts, burnishing alone often is enough.

Polish the contact and remove any residual material with a contact burnishing tool.

Or use our premium, long-lasting, non-residual diamond spatulas (available in a 3-piece kit). These are the most popular, longest lasting, and in the long run, most economical tools. See below.

Most mechanics prefer to use the flex files for older, larger contacts. Some like to use the non-conductive A-5615K1, K2, and K3 on newer, smaller relays such as Westinghouse ES, Otis Slimline and Automatic electric.

SAFETY NOTE:
Since burnishing tools are conductive, they must be used with the power off!



ORANGE STICKS

Dozens of practical uses. Especially useful for cleaning contacts. Sold in bags of ten.

A560W6 Orange sticks

CONTACT BURNISHING TOOLS (10/PK)

Adams part no.	Dimensions		
	L	W	Thick
A561B1	4"	3/16"	0.007"
A561B2	3 5/8"	1/4"	0.010"

PLASTONE FLEXIBLE FILES (12/PK.)

Adams part no.	Dimensions			Grit
	L	W	Thick	
A5615A1	4 1/2"	1/4"	0.015"	240
A5615A2		3/8"		240
A5615A3		1/4"		320
A5615A4		3/8"		320
A5615B1	4 3/4"	3/8"	0.025"	120
A5615C1		1/2"		180
A5615C2		1/4"		240
A5615C3	4 1/2"	3/8"	0.020"	240
A5615C4		1/4"		320
A5615C5		3/8"		320
A5615D1		1/4"		180
A5615D2		3/8"		180
A5615D3		1/4"		240
A5615D4	3/8"	240		
A5615D5	1/4"	320		
A5615D6	3/8"	320		
A5615E1	4 3/4"	3/8"	0.040"	80
A5615E2		1/2"		80
A5615E3		1/2"		120
A5615E4		1/2"		180
A5615E5	4 1/2"	1/2"	0.040"	240
A5615E6		1/2"		320
A5615F1		7/8"		80
A5615F2		7/8"		120
A5615F3		7/8"		180
A5615F4		7/8"		240
A5615F5	7/8"	320		
A5615G1	4 3/4"	1/2"	0.070"	80
A5615G2		1/2"		120
A5615G3		1/2"		180
A5615G4		1/2"		240
A5615G5		1/2"		320
A5615H1	4 1/2"	3/8"	0.070"	120
A5615H2		3/8"		180
A5615H3		3/8"		240
A5615H4		3/8"		320
A5615J1	4 1/2"	7/8"	0.020"	80
A5615J2		7/8"		120
A5615J3		7/8"		180
A5615K1		1/8"		320
A5615K2	4 1/2"	1/8"	0.020"	240
A5615K3		1/8"		180

DIAMOND SPATULA KIT & INDIVIDUAL FILES

Adams part no.	Description
A5616A4	3-piece spatula kit, incl. 1 ea. coarse, medium, and fine spatula
A5616A1	Coarse-grit spatula (green handle)
A5616A2	Medium-grit spatula (red handle)
A5616A3	Fine-grit spatula (blue handle) Grit on one side only.

RUFF LITE (110VAC)

A 14125 RUFF LITE

13W Fluorescent lamp (900 Lumens) W-25-FT. Power cord (18/2 SJTOW-A). IN-line ballast; internal switch moisture-proof housing.

Maverick (110VAC)

A 14325 MAVERICK

13W Fluorescent lamp (900 Lumens) W-25-FT. Power cord (18/2 SJTOW-A). Magnified end light works like a flashlight to direct light where needed most. Bulb is protected by cushion and bumper. Switch and ballast in handle.

A 14425 TOOL TAP

Same as A 14325, Plus tool tap for powering tools or additional lights; 16/3 power cord.

A 14400 CONVERSION HEAD

Conversion Head with internal switch and ballast. A 14325 lamp head connects to your cordset.

A 14412 TOOLBOX LIGHT

Maverick-style toolbox light; same as A 14325 with 12" cord that connects to your power extension cord.

A 14520 STD.-CORD GO LITE

13W maverick-style fluorescent lamp with switch in lighthead. Cigarette plug on 20-ft. 18/2 SJTOW-A standard cord. uses battery pack shown on other side.

Go Lite (12V)

A 14521 COILED-CORD GO LITE

Same as A 14520 with 2-10 ft. coiled cord, 18/2 tpe. not shown.

A14700 GO LITE BATTERY PACK

7-AMP Battery pack with 2-stage charger. Wear over the shoulder or around waist. Take with you to your boat or RV battery life up to 5.5 hours, continuous use. Cigarette jack accepts 12-volt Go Lite plug. Attach to AC adapter (included) to recharge.

AC Adapter also recharges cell phones & walkie-talkies!

A14001 MAGNETIC CLAMP

Magnetic Mount Clamps onto outer tube of lamp; lamp can be rotated freely to illuminate work area. Keeps your hands free for the task at hand.

A14003 MAGNETIC HOOK

Same as A 14001, Plus a rotating plastic hook. Clamp onto outer lamp tube and suspend from hook or support on ferrous surface with magnet

A14004 REPLACEMENT BLUB FOR ALL MODELS

Replacement rough-service bulb for Ruff Lite, Maverick, and Go Lite. Not shown.



A14125



A14325



A14425



A14400



A14412



A14520



A14700



A14001

TRIPLETT DIGITAL MULTIMETERS



A106D05 Digital Multimeter

- ▲ 3 1/2 Digit, 1999 max. reading
- ▲ HUGE, 1.15" High Digital Display
- ▲ Manual Range Selection
- ▲ Data Hold
- ▲ DC Voltage to 1000V
- ▲ AC Voltage to 750V
- ▲ AC/DC Current to 10A
- ▲ Resistance to 200M Ω
- ▲ Continuity Test
- ▲ Diode Check
- ▲ Transistor Check
- ▲ Auto Polarity
- ▲ Overload Protection
- ▲ Low Battery Indication
- ▲ Auto Power Off
- ▲ Double Insulated Case
- ▲ Safety designed to comply with IEC 1010-1
- ▲ CAT I, II, and III Rated
- ▲ Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips & 9 Volt Battery


Triplet: Model 9005-A  

A106D26 Digi-Probe Multimeter with Logic

- ▲ Large 3200 Count High Contrast LCD
- ▲ 32 Segment Bargraph
- ▲ 5 DC Voltage Ranges
- ▲ 4 AC Voltage Ranges
- ▲ 2 DC Current Ranges
- ▲ 2 AC Current Ranges
- ▲ 6 Resistance Ranges
- ▲ Logic Test
- ▲ Diode Test
- ▲ Continuity Check



- ▲ Autoranging
- ▲ Data Hold
- ▲ Range Hold
- ▲ Low Battery Indication
- ▲ Auto Power Off



- ▲ Reversible Safety Probe Tip - can be safely stored when not in use
- ▲ Uses 2 - 1.5V AAA Batteries (included)

Triplet: Model 3526-B

A106D15 Digital Multimeter with Temperature & Capacitance

- ▲ 3 1/2 Digit, 1999 max. reading
- ▲ HUGE 1.15" High Digital Display
- ▲ Manual Range Selection
- ▲ Data Hold
- ▲ DC Voltage to 1000V
- ▲ AC Voltage to 750V
- ▲ AC/DC Current to 10A
- ▲ Resistance to 200M Ω
- ▲ Temperature Test (Probe Included)
- ▲ Capacitance Test (Extension Lead Included)
- ▲ Frequency
- ▲ Continuity Test
- ▲ Diode Check
- ▲ Transistor Check
- ▲ Auto Polarity
- ▲ Overload Protection
- ▲ Low Battery Indication
- ▲ Auto Power Off
- ▲ Double Insulated Case
- ▲ Safety designed to comply with IEC 1010-1
- ▲ CAT I, II, and III Rated
- ▲ Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips, Thermocouple Probe, Capacitance Extension Lead & 9 Volt

Triplet: Model 9015-A  

All 9000 Series
Triplet Digital
Multimeters
come with the
manufacturer's
3-year Warranty



A106D25 Autoranging Digital Multimeter with Capacitance & Frequency

- ▲ 3 3/4 Digit, 3260 max. reading
- ▲ 33 Segment Bargraph
- ▲ Auto / Manual Range Selection
- ▲ DC Voltage to 1000V
- ▲ AC Voltage to 750V
- ▲ AC Current to 10A
- ▲ AC/DC Current to 10A
- ▲ Resistance to 32.6M Ω
- ▲ Frequency
- ▲ Capacitance Test
- ▲ Continuity Test
- ▲ Diode Check
- ▲ Transistor Check
- ▲ Data Hold
- ▲ Auto Power Off
- ▲ Double Insulated Case
- ▲ Safety designed to comply with IEC 1010-1
- ▲ CAT I, II, and III Rated
- ▲ Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips & 9 Volt Battery

Triplet: Model 9025



Affordable Clamp-Ons for Today's Maintenance Needs.

- ▲ Three Models, all CE marked. Tested to IEC 1010 Category III 600V
- ▲ Clamps fit 1 - 750 MCM or 2 - 350 MCM cables
- ▲ Rugged - designed to MIL-T-28800 for a Class II Instrument
- ▲ Double Insulated Design



**A106E00
AC Clamp-On Meter**

- ▲ 3 1/2 LCD with max. reading of 1999
- ▲ CAT III 600V
- ▲ AC Current Measurement to 1000A
- ▲ AC/DC Voltage Measurement to 600V
- ▲ Resistance Measurement to 200Ω
- ▲ Backlit Display
- ▲ Ergonomic Design with Tear Drop Shaped Jaw
- ▲ Average AC Responding Measurements
- ▲ Diode & Continuity Test
- ▲ Manual Ranging
- ▲ Data Hold
- ▲ Three Year Warranty

Triplet: Model 9300-A

**A106E10
AC/DC Clamp-On Meter**

- ▲ 3 3/4 LCD with max. reading of 3999
- ▲ CAT III 600V
- ▲ AC/DC Current Measurement to 1000A
- ▲ AC/DC Voltage Measurement to 600V
- ▲ Resistance Measurement to 40MΩ
- ▲ Temperature from -4° to 1472° F
- ▲ Capacitance Ranges from 40nF to 100µF
- ▲ Frequency Ranges from 10Hz to 10MHz
- ▲ Duty Cycle Test
- ▲ Diode & Continuity Test
- ▲ Backlit Display
- ▲ Ergonomic Design with Tear Drop Shaped Jaw
- ▲ Average AC Responding Measurements
- ▲ Relative Mode
- ▲ Auto Zero on DC Current Measurements
- ▲ Auto / Manual Ranging
- ▲ Auto Power Off
- ▲ Three Year Warranty

Triplet: Model 9310-A



**A106E20
True RMS AC/DC Clamp-On Meter**

- ▲ 3 3/4 LCD with max. reading of 3999
- ▲ CAT III 600V
- ▲ True RMS Measurements (45Hz to 1KHz)
- ▲ AC/DC Current Measurement to 1000A
- ▲ AC/DC Voltage Measurement to 600V
- ▲ Resistance Measurement to 40M
- ▲ Temperature from -4° to 1472° F
- ▲ User Selectable ° F or ° C
- ▲ Capacitance Ranges from 40nF to 100µF
- ▲ Frequency Ranges from 10Hz to 10MHz
- ▲ Measures Clamp-On Frequency (25Hz to 400Hz)
- ▲ Min/Max Hold
- ▲ Duty Cycle Test
- ▲ Diode & Continuity Test
- ▲ Backlit Display
- ▲ Ergonomic Design with Tear Drop Shaped Jaw
- ▲ Relative Mode
- ▲ Auto Zero on DC Current Measurements
- ▲ Auto Power Off
- ▲ Three Year Warranty

Triplet: Model 9320-A

Each Model 9000 Series Clamp-On includes a zippered, vinyl carrying case, test leads, screw-on alligator clips, battery and instruction manual. The 9310-A and 9320-A also includes a K-Type Thermocouple Adaptor and Probe.

TRIPLETT AC TEST EQUIPMENT

**A106ESIA
Sniff-It Rev A
Non-Contact, AC Voltage Detector**

- ▲ New Ergonomic Design!
- ▲ Detects AC Voltage without making contact
- ▲ Sensitivity from 30 to 600 Volts AC
- ▲ Light flashes & beeper chirps when AC voltage is present
- ▲ Beep Rate Indicates the Magnitude of Voltage (low or high voltage)
- ▲ Flashes & Beeps faster as AC voltage is approached
- ▲ Economical, Non-Contact probe is safe and simple to use
- ▲ Pocket-Sized with Pocket Clip
- ▲ Powered by one A23 Battery (included)
- ▲ 5 Year Limited Warranty

Uses for the Sniff-It:

- ▲ Tests for AC Voltage on:
 - ▲ Outlets
 - ▲ AC Motors
 - ▲ Light Bulb Sockets
 - ▲ Light Switches
 - ▲ Extension Cords
 - ▲ House Trailer Siding
 - ▲ Appliances
 - ▲ Circuit Breakers
 - ▲ Power Tools
- ▲ Identify "hot" side of AC receptacles
- ▲ Find and trace electrically "live" wires or objects
- ▲ Determine if metal surfaces are "live" or "ground"
- ▲ Detect presence of high voltage electric fields
- ▲ Detect "ringing" telephone lines
- ▲ Test fuses (axial type)
- ▲ Find breaks in AC wiring
- ▲ Many, many more . . .

Specifications

Range: 30 to 600 volts AC, 60Hz
 Indicators: Audible beeper and flashing red LED
 Battery: 1 - A23 or 23A (12 Volts) (Included)
 Body Size: 5.8" (L) x 1.25" (W) x 0.8" (H)
 Weight: Approx. 0.2 lb.

Triplet: Model 9600 Sniff-It Rev A



**A106ESI2
Sniff-It 2
Non-Contact, AC Voltage Detector
with Adjustable Sensitivity Control**

- ▲ Detects AC Voltage without making contact
- ▲ Variable Sensitivity, from 5 to 600 Volts AC
- ▲ Light flashes & beeper chirps when AC voltage is present
- ▲ Flashes & Beeps faster as AC voltage is approached
- ▲ Economical, Non-Contact probe is safe and simple to use
- ▲ Pocket-Sized
- ▲ Power Beeper Reminder
- ▲ Powered by one A23 Battery (included)
- ▲ 5 Year Limited Warranty

Uses for the Sniff-It 2:

- ▲ Tests for AC Voltage on:
 - ▲ Outlets
 - ▲ AC Motors
 - ▲ Light Bulb Sockets
 - ▲ Video Surveillance Camera Power
 - ▲ Extension Cords
 - ▲ Telephone and Cablevision
 - ▲ Appliances
 - ▲ Light Switches
 - ▲ Power Tools
 - ▲ House Trailer Siding
 - ▲ Circuit Breakers
- ▲ Detects power line voltage: 120, 220, 480 & 600 VAC
- ▲ Detects control voltage: 12 & 24 VAC
- ▲ Identify "hot" side of AC receptacles
- ▲ Find and trace electrically "live" wires or objects inside walls
- ▲ Determine if metal surfaces are "live" or "ground"
- ▲ Detect presence of high voltage electric fields
- ▲ Detect "ringing" telephone lines
- ▲ Many, many more . . .

Specifications

Range: 5 to 600 volts AC, 60Hz
 Indicators: Audible beeper and flashing red LED
 Battery: 1 - A23 or 23A (12 Volts) (Included)
 Body Size: 5.8" (L) x 1.25" (W) x 0.8" (H)
 Weight: Approx. 0.2 lb.

Triplet: Model 9601 Sniff-It 2

The New, Improved 9000 Series Clamp-Ons have many new features including Backlit Displays - Plus Temperature, Capacitance and Frequency on Select Models!



TRIPLETT SPECIALTY TESTERS

A106PT6 ProTemp 6 Non-Contact, Infrared Thermometer



- ▲ 6:1 Measurement Ratio
- ▲ Streamlined, Ergonomically Styled Case
- ▲ Cool Blue Backlit Display
- ▲ Non-Slip Finger Treads
- ▲ Not "Gun Shaped" like competitors models
- ▲ Laser Pointer pinpoints center of measurement area
- ▲ Simple, One-Button Operation
- ▲ 0° to 605° F (-18° to 315° C)
- ▲ User Selectable ° F or ° C Display
- ▲ Holds Reading Automatically for 7 Seconds
- ▲ Auto Power Off
- ▲ Fixed Emissivity (0.95)
- ▲ Battery Level Indicator
- ▲ Operates from a standard 9 Volt Battery
- ▲ One Year Warranty

Specifications

Temperature Range:	0° to 605° F (-18° to 315° C)
Operating Temperature:	50° to 125° F (10° to 52° C)
Resolution:	1° F (1° C)
Accuracy:	77° to 500° F (25° to 260° C) ± 2% of reading or 3° F (2° C) plus one digit, whichever is greater
	30° to 76° F (0° to 24° C) ± 3% of reading or 5° F (3° C)
	0° to 29° F (-18° to -1° C) ± 4% of reading or 7° F (4° C)
Response Time:	500 mSec, 95% Response
Target Size/Field of View:	6:1 optics ratio with a 1" minimum target
Repeatability:	2% of reading, or 3° F (2° C)
Spectral Response:	7-18 um
Emissivity:	Fixed at 0.95
Relative Humidity:	10-95% RH noncondensing, @ up to 86° F (30° C)
Storage Temperature:	-4° F to 150° F (-20° to 65° C) without battery
Battery:	1 - 9 volt Alkaline Battery
Battery Life:	12 Hours Continuous Operation
Dimensions:	7.25" x 1.75" x 1.5"
Weight:	4.8 oz.

Triplet: Model ProTemp 6



A106TDR Triplet TDR Cable Fault Finder

- ▲ Find Cable Length or Distance to Fault from ONE END!
- ▲ Low Cost Digital Cable Length Meter/TDR
- ▲ Built-in Tone Generator for Cable Tracing & Identification
- ▲ Simple Operation with Automatic Distance Display
- ▲ Internal Library of 39 Standard Cable Types
- ▲ Suitable for testing all types of Communication Cables
- ▲ Compact, Ergonomic Design, weighs less than 8 oz.
- ▲ Padded Cordura Holster included
- ▲ Three Year Warranty

Triplet TDR

Triplet TDR Specifications:
Approximate Range:

Resolution:	Coaxial Cable 6400 ft
	Structured Wiring 2500 ft
	Telephone Cable 2500 ft
Accuracy:	1 ft < 300 ft & 3 ft > 300 ft
	± 2 feet - Cables up to 10 ft
	± 5 feet - Cables 10 to 200 ft
	± 3% - Cables longer than 200 ft
Cable Library:	39 Standard Cable Types
Output Impedance:	50, 75 & 100 Ohms
Velocity of Propagation:	Adjustable 0 to 99%
Tone Generator:	Oscillating 810 - 1110Hz
Display:	Dot Matrix LCD

Connector Type:	BNC
Power Supply:	1 - 9 Volt Battery
Battery Life:	Approx. 2000 Tests
Operating Temperature:	5 to 122 deg. F
Storage Temperature:	-4 to 158 deg. F
Dimensions:	8 x 3 x 1.5 inches
Weight:	8 oz.
Safety:	IEC61010-1, EN 60950
EMC:	BS/EN 61326-1
Includes:	Padded Cordura Holster, Test Lead, Adaptor w/ Alligator Clip, 9V Battery



A106FOX The Original Fox Tone Generator



- ▲ Generates 3 distinct tones usable for wire tracing
- ▲ Performs a variety of tests on telephone lines
- ▲ Line powered in Tone Mode
- ▲ LED Indicator for continuity
- ▲ Supplies "Talk Power" to allow communicating between handsets (talksets) or powering a telephone
- ▲ Alligator clips and modular plug allow for connection to stripped wires, terminal panels, or a standard modular jack (single line)
- ▲ Powered by a standard 9V battery (not included)
- ▲ Works with Hound, Hound 2 or Hound 3 Probe Inductive Tracers
- ▲ One Year Warranty

Triplet: Fox

A106 Hound The Hound 3 Probe Streamlined Inductive Tracer with Headlights and Earphone Jack



- ▲ New Headlights to help light your way in dark areas and reduce florescent light noise
- ▲ Streamlined Design allows for better access in hard-to-reach areas
- ▲ New Shielded Design to suppress "Feedback Squeal"
- ▲ Bandpass Filter to suppress 60Hz and Hi Frequency Noise
- ▲ Earphone Jack for use in quiet or noisy environments.
- ▲ Improved Sensitivity and Loudness
- ▲ Includes New Conductive Duck-Bill Tip for Safer, Easier Penetration in cable bundles - Metal tip also included
- ▲ Easy Access Battery Door
- ▲ Adjustable volume / sensitivity control
- ▲ LED gets brighter as the signal gets stronger - LED indication even works when Earphones are used!
- ▲ Contains a hi-gain, hi-impedance amplifier
- ▲ Capable of identifying the Fox's tone up to 12 inches away
- ▲ Rugged, moisture resistant, mylar cone speaker
- ▲ Use with the Fox 2, Fox, TDR or WireMaster XR-2 for quick & efficient wire tracing
- ▲ Powered by a standard 9V battery (not included)
- ▲ One Year Warranty

Triplet: Hound 3

A724H3 Fox & Hound 3 Probe Kit



Includes:

- ▲ Original Fox Tone Generator
- ▲ Hound 3 Probe Inductive Tracer
- ▲ Cordura Carrying Case

Triplet: Cat No. 3397

TRIPLETT COMPACT TEST EQUIPMENT



A106D30
Autoranging, Pocket-Sized DMM

- ▲ 3 3/4 Digit, 4000 Count Display
- ▲ Auto / Manual Ranging
- ▲ AC/DC Volts to 600V
- ▲ AC/DC Current to 400mA
- ▲ Resistance to 40MΩ
- ▲ CAT II 600V Rating on Voltage Ranges
- ▲ Capacitance Test to 100μF
- ▲ Frequency Range to 10KHz
- ▲ Duty Cycle
- ▲ Diode Check
- ▲ Continuity Beeper
- ▲ Relative Mode
- ▲ Data / Range Hold
- ▲ Auto Power Off
- ▲ Low Battery Indicator
- ▲ One Year Warranty

Triplet: Model 2030-C.

The Model 2030-C features a protective cover with rugged hinge design which can be completely folded back, or form a stand for better viewing. The unique "Power Slot" ensures that you turn your tester off before closing the lid, therefore saving battery life! A handy wrist strap is also included.



A106D
Compact DMM with Backlit Display & Temperature Test

- ▲ 3 1/2 Digit, w/ 1999 max. reading
- ▲ Backlit Display
- ▲ AC/DC Voltage to 500V
- ▲ AC/DC Current to 10A
- ▲ Temperature Test (Probe Included)
- ▲ Resistance to 20MΩ
- ▲ Continuity Test
- ▲ Diode Check
- ▲ Transistor Check
- ▲ Data Hold
- ▲ Double Insulated Case
- ▲ CAT I and II Rated
- ▲ Overload Protected
- ▲ Three Year Warranty
- ▲ Includes: Red Rubber Boot, Safety Test Leads with Screw-On Alligator Clips, Thermocouple Probe & 9 Volt Battery

Triplet: Model 1101-A



A106EMINI
Mini AC Clamp-On Meter

- ▲ Economical, Compact AC Current Clamp-on
- ▲ Simple, One Button Operation
- ▲ Measures from 0 to 200 Amps AC in Two Ranges
- ▲ Large, 3 3/4 Digit, 4000 Count Display
- ▲ Autoranging
- ▲ Data Hold
- ▲ Overload Indication (@ 400A)
- ▲ Auto Power Off
- ▲ Low Battery Indication
- ▲ Powered by one 3V Battery (2 included)
- ▲ Carrying Case, Wrist Strap and Spare Battery included
- ▲ 1 Year Limited Warranty

Triplet: Model 9200

A106A
The favorite Hand-Held Analog VOM in the Maintenance and Telecommunications field



Adams Part No.	Description
A106F	369 Carrying Case
A106F369V	369-V Padded vinyl carrying case
A106F9000	Padded vinyl carrying case
A106FTDR	Durable cordura case, velcro closure
A106FFOX	Durable cordura case, velcro closure
A106G	42" Test Leads with attachable alligator clips
A106GDMM	48" Test Leads with attachable alligator clips
A106J	1/16-amp fuse
A106P	1/16-amp fuse
A106K	9-volt alkaline battery
A106L	1.5 volt battery
A106M	15 volt battery
A106N	12 volt battery
A106NSNIFF	12 volt battery, A23 size
A106U	0.5 Amp/250 Volt fuse
A106U1101-A	300mA / 500 V, 5 X 20 mm fuse

Triplet Accesories

For Model(s)	Triplet Part No.
310, 1101-A	10-1258
310, 1101-A	10-2959
9000-series DMMs and clamp-ons	10-4289
TDR	10-4249
Fox & Hound Series	10-3983
310	79-153
9000-series & 1101-A	79-760
310 (Type 6 or earlier)	3207-37
310 (Type 7)	3207-112
9000-series, 1101-A, TDR, PT6, Fox/Hound	37-48
310	37-21
310 (Type 5 & earlier)	37-22
310 (Type 6 & 7 only)	37-60
Sniff-It (A), Sniff-It 2	37-67
1101, 2202, 3303	3207-91
1101-A	3207-130

Model 310

- ▲ 18 Ranges and Functions
- ▲ AC/DC Voltage to 1200V
- ▲ DC Current to 0.6A
- ▲ Resistance to 20MΩ
- ▲ Drop Resistant, High-Impact Case
- ▲ Diode Overload Protected Meter
- ▲ Fused Resistance Ranges
- ▲ Single Enclosed Range Switch
- ▲ 3 Year Warranty

Triplet: Model 310



Model A106C

Comes complete with everything you need for maintenance testing including:

- ▲ Model 310
- ▲ Model 10 AC Clamp-On
- ▲ Model 101-G Line Separator
- ▲ 42" Separating Leads
- ▲ 42" Safety Test Leads
- ▲ Screw-On Alligator Clips
- ▲ Model 379 Carrying Case
- ▲ Batteries & Instruction Manual

Triplet: Model 100 (w/ Model 310 & 10)

EXTECH MULTIMETERS



Adams Part #A107D
(Extech Part #ET34)

Adams A107D Voltage and Continuity Tester

LED indication of AC/DC voltage to 480V in seven ranges

- ▲ Bright indicating LEDs at 12, 24, 120, 208, 240, 277 and 480
- ▲ Audible and visible continuity test up to 200kΩ
- ▲ Single pole live voltage detector
- ▲ Voltage function operates without batteries
- ▲ Cat III-600V
- ▲ Complete with 39" cable with test probe and two AAA batteries



Adams A107A Autoranging Digital Multimeter

Rugged compact design with Temperature, Frequency and Capacitance functions

- ▲ Autoranging with manual range override
- ▲ Relative Zero, Data Hold, Auto Power Off, Range Hold
- ▲ Includes protective holster with stand, two AA batteries, test leads and temperature probe

Adams Part #A107A
(Extech Part MN26)

SPECIFICATIONS

Display Counts	4000
AC/DC Voltage Ranges	400mV, 4V, 40V, 400V, 600V
Basic DCV Accuracy	±1.0%
AC/DC Voltage Ranges	400 μA, 4000 μA, 40 mA, 400 mA, 10 A
Resistance Ranges (W)	400, 4K, 40K, 4M, 40M
Capacitance Ranges	4 nF, 40 nF, 400 nF, 4 μF, 200 μF
Frequency	10Hz to 10MHz
Temperature	0 to 1400°F (0 to 760°C)
Duty Cycle	0.1% to 99.9%
Diode/Continuity	Yes
UL Rating	CatIII-600V
Dimensions/Weight	4.8" x 2.4" x 1.6" / 9.17oz

Adams A107P/A107Q Manual Ranging Multimeter

General purpose multimeters-Model EX411 provides True RMS readings

- ▲ Easy to read large backlit display
- ▲ True RMS AC measurements (EX411)
- ▲ Type K thermometer built-in for surface or air temperature measurements
- ▲ Input fuse protection and mis-connection warnings with audible and visible signs
- ▲ Data hold freezes display reading
- ▲ Ergonomically designed to fit comfortably in your hand
- ▲ Complete with CAT III test leads, multi-position tilt stand, hanging strap, holster with test lead storage, bead wire temperature probe and 9V battery



Adams Part #A107P
(Extech Part #EX410)

SPECIFICATIONS

Display Counts	2000
True RMS	Model EX411
AC Voltage Ranges	2V, 200V, 600V
DC Voltage Ranges	200mV, 2V, 200V, 600V
Basic DCV Accuracy	±0.5% (±0.3% EX411)
AC Current Ranges	200mA, 20A
DC Current Ranges	200 μA, 200 mA, 20 A
Resistance Ranges (W)	200, 2000, 20k, 200k, 20M
Temperature	-4 to 1382°F (-20 to 750°C)
Duty Cycle	0.1% to 99.9%
Diode/Continuity	Yes
UL Rating	Cat III-600V
Dimensions/Weight	7.4" x 3.2" x 2" / 0.75lbs



Adams Part #A107Q
(Extech Part #EX411)

EXTECH IR THERMOMETERS

Adams A107F/A107S
Autoranging Multimeters + IR Thermometers
Autoranging multimeters with the convenience of a built-in IR thermometer

Common Features:

- ▲ Non-Contact infrared thermometer measures surface temperature of objects unsafe to contact or difficult to reach
- ▲ Infrared features 8:1 distance to target ratio with 0.95 fixed emissivity
- ▲ Easy to read large backlit display
- ▲ Complete with CAT III test leads, multi-position tilt stand, hanging strap, holster with test lead storage, 9V battery and Type K thermometer probe (EX470 only)

EX470 Additional Features:

- ▲ True RMS voltage and current readings
- ▲ Built-in Type K thermometer
- ▲ Capacitance, Frequency and Duty Cycle functions



Adams Part #A107S
(Extech Part #EX450)

Adams Part #A107F
(Extech Part #EX470)

SPECIFICATIONS		
Model	A107S/ EX450	A107F/ EX470
Display Counts	2000	4000
True RMS	No	Yes
DC Voltage Ranges	0.1mV to 600V (DC)	0.1mV to 600V
AC Voltage Ranges	1mV to 600V (AC)	0.1mV to 600V
Basic DCV Accuracy	±0.5%	±0.3%
AC/DC Current Ranges	0.1mA to 20A	
Resistance Ranges (W)	0.1W to 20MW	0.1W to 40 MW
Capacitance Ranges	—	0.01nF to 100mF
Frequency	—	5.000Hz to 10.00MHz
Duty Cycle	—	0.1 to 99%
Temperature (Type K)	—	-4 to 1382°F (-20 to 750°C)
Temperature (Infrared)	-4 to 518°F (-20 to 270°C)	
Diode/Continuity	Yes	
UL Rating	Cat III-600V	
Dimensions/Weight	7.4" x 3.2" x 2" / 0.75lbs	

Non-Contact IR Thermometers
Provide fast, easy and accurate readings for most surface temperature measurements

- ▲ Simply point at objects being measured
- ▲ Laser point provides aim
- ▲ Ideal for measuring hot spots in electrical panels
- ▲ Automatic data hold when trigger is released
- ▲ Fixed 0.95 emissivity covers 90% of surface applications
- ▲ Complete with battery

SPECIFICATIONS		
Model	A107AB / IR201	A107C/ 42510
Range	-58 to 518°F (-50 to 270°C)	-58 to 1000°F (-50 to 538°C)
Basic Accuracy	±2.5%	±2%
Max RPM Resolution	1	0.1<200
Emissivity	0.95	0.95
Field of View (distance to target)	6:1	8:1
Backlit Display	No	Yes
Battery	Two AAA	One 9V
Dimensions	3.7" x 2" x 1"	3.2" x 1.6" x 6.3"
Weight	2.7oz	6.4oz



Adams Part #A107AB
(Extech Part #IR201)

Adams Part #A107C
(Extech Part #42510)

EXTECH AC METERS & TACHS



Adams' Part #A107I
(Extech Part #38389)

Adams' A107I 600A True RMS AC/DC Clamp Meter

Autoranging with Capacitance and Frequency functions

- ▲ AC/DC Current readings with resolution of 0.1A
- ▲ 1.25" jaw size accommodates conductors up to 350MCM
- ▲ Peak Hold
- ▲ Auto Power Off and Data Hold
- ▲ Complete with test leads, temperature probe, 9V battery and belt holder



Adams' Part #A107B
(Extech Part MA200)

Adams' A107B Mini Clamp-on Meter

Compact size enables measurements in tight spaces

- ▲ Clamp-on measures AC current to 400 A with 0.01A resolution
- ▲ 0.9" jaw size
- ▲ Measures AC/DC Voltage up to 600V
- ▲ Measures resistance up to 400 W
- ▲ Continuity beeper and Diode Test
- ▲ Complete with test leads, two AA batteries and carrying case

SPECIFICATIONS	
Display Counts	4000
AC Voltage Ranges	4V, 40V, 400V, 600V
DC Voltage Ranges	400mV, 4V, 40V, 400V, 600V
Basic DC Current Accuracy	±2.5%
AC/DC Current Ranges/MAX Resolution	400A, 600A (0.1A)
Resistance Ranges (W)	400, 4k, 40k, 400k, 4M, 40M
Capacitance Ranges	40nF, 400nF, 4mF, 40mF, 100mF
Temperature (Infrared)	-4 to 1400°F (-20 to 760°C)
Diode/Continuity	Yes
UL Rating	Cat II-600V
Dimensions/Weight	8" x 3.1" x 1.6" / 6.5ozs

Adams' A107U/A107X Mini Tachometers

For RPM and surface speed measurements

- ▲ Pocket size housing with protective finger guard
- ▲ Hold button freezes displayed readings
- ▲ 461700 Photo tachometer measures RPM without contact up to 6" distance
- ▲ 461750 Contact model measures RMP and surface speed
- ▲ Complete with 9V battery – 461700 includes reflective tape and 461750 includes wheels for RPM and surface speed measurements

SPECIFICATIONS		
Model	A107X / 461700	A107U / 461750
Range	rpm 10 to 99,999	10 to 9,999
	feet/min -	3 to 6560
	meters/min -	1 to 1999.9
	yards/min -	1 to 5000
Basic Accuracy	±(0.1% reading + 2 digits)	
Dimensions	4.9" x 2" x 1.3"	5.9" x 2" x 1.3"
Weight	4oz	5oz



Adams' Part #A107U
(Extech Part #461750)



Adams' Part #A107X
(Extech Part #461700)



Water/Temp Resistant Grease is characterized by exceptional mechanical stability, very high load-carrying ability, excellent resistance to water, oxidation and corrosion, with excellent performance in high-low temperature environments.

Our premium-quality grease features excellent pumpability and dispensing properties, and is therefore suitable for low-temperature application. *Contains no molybdenum sulfide.*

APA100CC Aerosol WTRG. 16-oz. cans, 6 cans/case only.

Silicone Spray is a clear lubricant suitable for use on all sliding and rubber surfaces. Recommended for doors, windows, rubber seals, moving cables, weather stripping, gears & sprockets.

Adams Silicone Spray eliminates squeaks, keeps rubber seals pliable, and promotes smooth movement of most rubber, plastic, and metal parts. It is non-staining and has excellent electrical resistance.

APA140CC Silicone Spray. 12-oz. cans, 6 cans/case only.

Solvent/Component Contact Cleaner is a strong degreaser formulated for general-purpose parts cleaning. Use on all metal surfaces and on oil-resistant rubber and plastic. Brush away loose oil and grease...spray Solvent onto parts to be cleaned...and wipe clean with rag or towel.

APA130CC Aerosol Solvent Parts Cleaner. 12-oz. cans, 6 cans/case only.

Chain & Cable Lubricant is a petroleum-base product compounded with graphite and additives to give the best possible lubrication to lift cables, pulleys, and chains. The lubricant penetrates dirt to saturate chain links and cable surfaces for maximum wear resistance and rust protection.

Graphite lubricates and prevents wear between wire rope strands long after the oil has been dispersed. Chain & Cable Lubricant also contains a rust preventative to protect against exposure to moisture. This product can increase wire rope life up to 300%.

APA180CC Chain & Cable Lubricant. 12-oz. cans, 6 cans/case only.

Guide Rail Lubricant applies a low-friction *dry lubricating film* that protects rails for extended periods against rust and corrosion. Sprayed rails do not require degreasing, a real time and labor saver. Also recommended for parts that need to be stored indefinitely, shipped overseas, or that may come into contact with salt or saltwater spray.

APA31CC Guide Rail Lubricant. 16-oz. cans, 6 cans/case only.

Heavy-Duty Penetrating Oil is a powerful penetrating catalyst that breaks through rusted joints and pipe threads with "capillary wet drilling action." It penetrates rusty, sticky, gummy, and frozen joints regardless of temperature. It displaces moisture, and even starts engines!

HD is a dissolving cleaner that lubricates while it works. It virtually pulls itself uphill, around, and into tight cavities and bearing surfaces. Use on industrial equipment to stop corrosion...on relays and other electrical equipment...business machines...elevator buffers...U-bolts, and more.

Pinpoint sprayer eliminates messy waste; works upside down and in all directions.

APA150CC Heavy-Duty Penetrating Oil. 16-oz. cans, 6 cans/case only.

Light Penetrating Oil is an excellent general-purpose lubricant for use in the shop and at the job site. Can also be used as a short-term rust inhibitor. Contains no graphite, molybdenum disulfide, etc.

APA160CC Light Penetrating Oil. 16-oz. cans, 6 cans/case only.



INDUSTRIAL ANTI-WEAR HYDRAULIC OIL

Adams Hydraulic Oil (HD32, HD46, & HD68) is designed for the lubrication and protection of industrial and mobile hydraulic equipment.

Adams Hydraulic Oil separates rapidly from water and is hydrolytically stable. It exhibits excellent oxidation, anti-friction and wear, filterability, & anti-corrosion properties.

Formulated with premium-quality paraffinic oils and proprietary additives; no barium, chlorine, lead, or silicone-type additives.

NOTE: Consult equipment operating manual for viscosity grade requirements.

Adams Hydraulic Oils meet or exceed these requirements:

- AFNOR E 48-603 • BF Goodrich 0152
- Cincinnati Machine P-68, -69, -70
- Commercial Hydraulic, except PM-500-series silver-containing pumps which require R & O-containing additives
- Denison HF-1, -02, -0 • DIN 51424, Part 2
- Ford M-61C13227 13
- General Motors LH-04-1, LH-06-1, LH-15-1
- Jeffrey No. 87 • Lee Norse 100-1
- Racine, variable-volume vane pumps
- U.S. Steel 127, 136 • Vickers I-286-S, M-2950-S

APO32GC HD32 Adams Hydraulic Oil, case of 4 1-gallon bottles

APO32P5G HD32 Adams Hydraulic Oil, 5-gallon pail

APO46GC HD46 Adams Hydraulic Oil, case of 4 1-gallon bottles

APO68HGC HD68 Adams Hydraulic Oil, case of 4 1-gallon bottles

RUST- AND OXIDATION-INHIBITED ELECTRIC MOTOR OIL

Adams Motor Oils (ISO#68, #100, & #150) are recommended for applications that require protection against rust and oxidation, but do not require anti-wear or extreme-pressure additives.

Use for lightly-loaded plain and anti-friction bearings, electric motors, machine tools, air compressors, and circulating systems where rust and oxidation are a concern. Also recommended as a gear oil where API GL-1 service is specified; also can be used as a non-detergent API SA motor oil.

Adams Motor Oil separates rapidly from water and is hydrolytically stable. It exhibits excellent foaming, anti-friction, filterability, and rust & corrosion protection properties. This formulation also features superior thermal and oxidative stability.

Formulated with premium-quality paraffinic oils and proprietary ashless additives. Contains no barium, chlorine, lead, or silicone-type additives.

NOTE: Consult equipment operating manual for viscosity grade requirements.

Adams Motor Oils meet or exceed the following industry requirements:

- AFNOR E 48-600 HL • API Service GL-1
- Cincinnati Machine P-38, -45, -54, -55, -57, -62 (note viscosity grades)
- Denison HF-1 • DIN 51524, Part 1 • U.S. Steel 126

APO68QC ISO #68 Adams Motor Oil, case of 12 32-oz. bottles

APO68GC ISO #68 Adams Motor Oil, case of 4 1-gallon bottles

APO100QC ISO #100 Adams Motor Oil, case of 12 32-oz. btls

APO100GC ISO #100 Adams Motor Oil, case of 4 1-gallon btls

APO150GC ISO #150 Adams Motor Oil, case of 4 1-gallon btls

APO32SC ISO #32 Adams Step Chain Oil, case of 6 1-gallon bottles



Adams Worm Gear Oil. Designed for lubricating and protecting heavily-loaded industrial and automotive worm gears operating at moderate to high temperatures. Especially recommended for bronze components that cannot tolerate typical sulfur-phosphorus gear oil additives.

Highly recommended for API GL-2 Service and wherever AGMA 7 Comp., 8 Comp, or 8A Comp is specified.

Formulated with premium-quality oils and proprietary additives. Emulsifies water, resists rust and foam, and is hydrolytically stable. Special oiliness additives ensure excellent lubricity and wettability. Contains no sulfur, phosphorus, barium, chlorine, or lead-type additives. Always follow manufacturer's recommendations for the worm gear drive you are servicing.

APO33GC Worm Gear Oil #680 in 1-gal. bottles, 4 gal./case only.

Adams EP Gear Oil. Extreme Pressure Industrial Gear Lubricant is designed for the lubrication and protection of industrial gears, including bevel, herringbone, planetary, and spur. Also recommended for plain and anti-friction bearings, enclosed gear units, gear reducers, and wherever an industrial extreme-pressure lubricant is specified.

Separates rapidly from water and is hydrolytically stable. Provides excellent protection from oxidation, friction, wear, extreme pressure, and corrosion. Always follow manufacturer's recommendations for the gear drive you are servicing.

Formulated from premium-quality paraffinic oils and proprietary ashless additives. Contains no barium, lead, or silicone additives.

Meets or exceeds the following:

- AGMA 9005-D94 • API GL-3 Service
- Cincinnati Machine P-35, P-59, P-63, P-74, P-76-78
- David Brown • DIN 51517 (3)
- General Motors LS-2 • US Steel 224

APO5GC EP Gear Oil #5 in 1-gallon bottles, 4 gal./case only.

APO150GGC EP Gear Oil #150 in 1-gallon bottles, 4 gal./case only.

Adams Chain Oil is recommended for escalator and man-lift drive chains. It clings to metal surfaces to reduce heat and inhibit rust. The good general lubricity of this product reduces chain wear and extends chain life.

Promotes free movement of chain links and helps reduce chain chatter. Also helps reduce strain on drive motors and keeps components moving freely and safely.

APO60QC Adams Chain Oil #60. 32-oz. bottle, 12 quarts/case only

APO60GC Adams Chain Oil #60. 1-gallon bottle, 4 gal/case only

AP032SC Adams Chain Oil #32 1-gallon bottle, 6 gal/case only

Adams Pit Pads are the most effective, economical way to clean up nuisance oil leaks. Their thirsty fibers are specially formulated to absorb leaking or spilled oil... but they will not absorb water.

Non-flammable Pit Pads replace 50 pounds of "kitty-litter"-type products. (Each 2-1/2 oz. pad is 16" x 20" x 1/4"-thick.)

Polypropylene Pit Pads can be stored indefinitely...even in humid conditions...without affecting their oil absorbency.

Improve the appearance and safety of machine rooms and pit work areas.

A629 Pit Pads, 100 pads/bag; 16 lbs. net wt

A single 100-pad package (just 16 lbs.!) absorbs up to 25-30 gallons of oil.





AP010GC **AP020GC** **AP0440GC** **AP0900GC**



APA150CC
APA160CC **AP0900QC** **AP0800QC** **AP050G**

Buffer Oil. For applications that require protection against rust and oxidation, but do not require anti-wear or extreme-pressure additives. Use for lightly-loaded plain and anti-friction bearings, electric motors, machine tools, air compressors, and circulating systems.

ISO #32: Used in moderate-load shock-absorbing devices. Low volatility reduces oil consumption, and prevents pressure build up.

ISO #68: For severe services where heavy continuous loading is common.

AP020GC Buffer Oil, ISO #32. 1-gallon bottle, 4 gallons/case only.

AP010GC Buffer Oil, ISO #68. 1-gallon bottle, 4 gallons/case only.

Door Closer Oil. Designed to lubricate and protect high-speed spindle bearings. Also used wherever an ISO 10 rust- and oxidation-inhibited hydraulic oil is specified.

Separates rapidly from water; hydrolytically stable. Provides excellent friction, filterability, rust and corrosion protection properties, as well as superior thermal and oxidative stability.

AP0440GC Door Closer Oil. 1-gallon bottle, 4 gallons/case only.

Brake Oil. This is a high-dielectric, highly-defined oil with a very low pour point.

AP0900GC Brake Oil, 1-gallon bottle, 4 gallons/case only.

Light Penetrating Oil is an excellent general-purpose aerosol lubricant for use in the shop and at the job site. Use as both a general lubricant and short-term rust inhibitor. Clean formula contains no excess graphite, molybdenum disulfide, etc.

APA160CC Light Penetrating Oil. 16-oz. aerosol can, 6 cans/case only.

Heavy-Duty Penetrating Oil is a penetrating aerosol catalyst that breaks through rusted joints and pipe threads with "capillary wet drilling action." Releases rusty, sticky, gummy, and frozen joints in any temperature. Displaces moisture...even starts engines!

APA150CC Heavy-Duty Penetrating Oil. 16-oz. aerosol can, 6 cans/case only.

Elevator Oil Refresher. This blend of plant extracts neutralizes hydraulic oil odors with its mild wintergreen fragrance. Use one quart per 50 gallons of hydraulic oil...more if necessary. Compatible with petroleum oils and additives found in hydraulic systems.

AP0900QC Elevator Oil Refresher. 32-oz. bottle, 12 quarts/case

Soft Stop "Anti-Chatter" Additive. This performance-improving fluid is a special friction modifier that enhances the flow characteristics of most hydraulic systems. It can relieve the "stick-slip" problem on noisy hydraulic cylinders. Not recommended for machines with common systems for hydraulic, transmission, and braking.

AP0800QC Adams Soft Stop Hydraulic Additive. 32-oz. bottle, 12 quarts/case only.

Non-Dripping Oil. This unique lubricant features ideas borrowed from several disciplines. Designed as a super penetrant and lubricant, it will not drip from chains, guides, or cables over areas where pedestrians will be concentrated.

It is non-corrosive to steel, brass, aluminum, and common plastics such as polypropylene, nylon, and PVC. Cleans contacted parts to insure proper lubrication and freedom of movement. For heavily-soiled or gummed parts, repeat applications or soaking may be necessary. Relatively high flash point and mild hazard profile.

AP050G Non-Dripping Oil. 4 gal./case.



Waterproof Grease. Our waterproof lubricating grease represents a new technology in wide-temperature, high-performance grease. In many applications, it outperforms high-temperature grease.

Contains no heavy metals, sulfur, phosphorus, chlorine, zinc, phenols, antimony, barium, or lead.

This calcium grease is designed for operation in wet or high-humidity conditions. It is suitable for lubricating bearings, bushings, rails, and open gears. Comes in 14-oz. cartridges for grease gun application.

APG702CTC Waterproof Lubricating Grease, ten 14-oz. cart./case.

APG700GG Grease gun for 14-oz. cartridges. Use w/**APG702CTC** Waterproof Lubricating Grease and **APG715CTC** All-Purpose Lubricating Grease. Order as many as you need. Grease Gun also available in Heavy Duty 10,000 psi. Order Part No. **APG700GGH**.

O-Ring Compound. Tacky material keeps O-rings in place during assembly. Apply sparingly by hand. Seal should be installed with coated side toward bottom of groove.

APG705TC O-Ring Compound, twelve 10-oz. tubes/case only.

All-Purpose Grease. Adams all-purpose grease is a lithium-based lubricating grease. It is formulated with the highest-quality base oils available, and is fortified with rust and oxidation inhibitors as well as extreme-pressure additives.

This versatile product has been manufactured to meet the multi-purpose needs of the elevator mechanic. Comes in 14-oz. cartridges for grease gun application.

APG715CTC All-Purpose Lubricating Grease, ten 14-oz. cart./case.

Wire Rope & Cable Lubricant is designed to clean, lubricate, and protect wire ropes and cables by removing dirt and reducing frictional forces. It aids in cleaning dirt, oil, and grease from surfaces. By removing accumulated dirt and oil, Wire Rope & Cable Lubricant reduces the abrasive wear among the wire rope strands.

Lubricant will not dry, and remains highly resistant to gum and varnish formation. The extremely low pour point eliminates oil coagulation at low ambient temperatures.

APG200GC Wire Rope & Cable Lubricant. 1-gal. btl, 4 gals/case.

Dash Pot Oil. Designed to lubricate and protect high-speed spindle bearings. Also used wherever an ISO 10 rust- and oxidation-inhibited hydraulic oil is specified.

Separates rapidly from water; hydrolytically stable. Provides excellent friction, filterability, rust and corrosion protection properties, as well as superior thermal & oxidative stability.

APO28BS Dash Pot Oil. 1-pint bottle.



Liquid Gasket. Brush on a replacement gasket with the built-in cap brush. Use only where operating temperature is 82°F (28°C) or less, internal pressure is less than 5 psi (35 kPa), and the gap does not exceed 0.08mm.

APC120CC Liquid Gasket, six 8-oz. cans/case only.

Cement. Our brush-on cement applies cleanly and easily with the built-in cap brush. Use on metal, rubber, plastic, glass, and wood. Apply to both surfaces to be bonded, let dry, then join.

APC130CC Contact Cement, six 8-oz. cans/case only.

Odorless Solvent/Cleaner/Degreaser. Clean, filterable fluid dissolves oil and grease from the dirtiest elevator components...with no strong odor.

Use in solvent stands or immersion tanks, or apply with brush, rags, or spray. Recycle indefinitely through a solvent reclaiming still.

APA948CC Odorless Solvent/Cleaner/Degreaser, 16-oz aerosol; 12 cans/case only.

APS948GC Odorless Solvent/Cleaner/Degreaser, 1-gallon bottle; 4 gal./case only.

APS948G5P Odorless Solvent Cleaner/Degreaser, 5-gallon pail.

Wypall® All-Purpose Wipers. Heavy-duty paper-fiber clean-up towels from Kimberly-Clark®. Use once, twice, three times...and toss. Low lint, high absorbency, great for jobsite clean-up chores, liquid or solid.

APC140C Heavy-Duty Wypall Shop Towels, 55/pkg., 18 bundles/case only.

Critical Task Wiper Towels. Low-abrasive paper wiping towels from Kimberly-Clark for electrical and other sensitive components that must be protected from scratches. Dispense from Kleenex®-type box.

APC150C Delicate Task Wipers, 15 boxes/case only.